


# Thermal Barrier Datasheet

## BB-45

ECD P/N: E44-4245-80



Temperature:	100°C [212°F]	150°C [302°F]	200°C [392°F]	250°C [482°F]	300°C [572°F]
Duration time:	79 min.	35 min.	23 min.	17 min.	13 min.
Max Operational Temp.:	The maximum operating temperature of the thermal barrier is 300°C [572°F]!				
Handling Details:	Cool thermal barrier to room temperature 25°C [77°F] before reuse.				



North & South America, Europe  
 ECD World Headquarters  
 4287-B SE International Way  
 Milwaukie, Oregon 97222-8825 U.S.A.  
 Tel: +1 503 659 6100 | + 1 800 323 4548  
 Fax: + 1 503 659 4422  
 E-Mail: sales@ecd.com | Web: [www.ecd.com](http://www.ecd.com)

ECD Asia/Pacific  
 Singapore  
 Mobile: +65 9692 6822  
 Fax: +65 6241 9890  
 E-Mail: [ecd.asia@ecd.com](mailto:ecd.asia@ecd.com)


ECD Europe/Africa/Middle East  
 Mobile: +48 512 659 100  
 E-Mail: [ecd.europe@ecd.com](mailto:ecd.europe@ecd.com)

- Top rated customer support • No-cost ECD Online Training • Award winning software •

# Thermal Barrier Datasheet

## BB-45

ECD P/N: E44-4245-80



Barrier Dimensions:	Height:	Width:	Length:	Weight:
	46mm [1.82"]	122mm [4.80"]	241mm [9.5"]	1.47kg [3.25lbs]



Figure 1 – External View



Figure 2 – Internal View



North & South America, Europe  
 ECD World Headquarters  
 4287-B SE International Way  
 Milwaukie, Oregon 97222-8825 U.S.A.  
 Tel: +1 503 659 6100 | + 1 800 323 4548  
 Fax: + 1 503 659 4422  
 E-Mail: [sales@ecd.com](mailto:sales@ecd.com) | Web: [www.ecd.com](http://www.ecd.com)

ECD Asia/Pacific  
 Singapore  
 Mobile: +65 9692 6822  
 Fax: +65 6241 9890  
 E-Mail: [ecd.asia@ecd.com](mailto:ecd.asia@ecd.com)

ECD Europe/Africa/Middle East  
 Mobile: +48 512 659 100  
 E-Mail: [ecd.europe@ecd.com](mailto:ecd.europe@ecd.com)

- Top rated customer support • No-cost ECD Online Training • Award winning software •