Products

Desoldering / Rework/SMD rework system /Jig

·IAK(0 FR-701 線







Safer and more secure rework operation with upgraded soldering and desoldering tools

2-in-1 unit for space saving

Compatible with N2 system by purchasing N2 iron

(FX-8802) as an optional accessary

Available in:

Other Countries

Contact Us

> Catalog

Features

Packing List / Specifications

Soldering Tip / Nozzle

Replacement Parts / Option

Features

Dual function rework station with FR-4101, 140W high power desoldering gun, and FX-8801, soldering iron, 2-in-1 unit for space saving

6 applications for a variety of soldering and desoldering works

Besides FR-4101, 140W desoldering gun, and FX-8801, soldering iron, 4 more applications are compatible with FR-701.

Tips (T18 and T19 series) and nozzles (N61 series) deliver excellent cost efficiency.





Soldering iron M type HAKKO FX-8801



With B tip



- Takes T18 tip series with improved thermal conductivity View the details

- 140 W high powers enable perfect desoldering for the components on multi-layer

- A wide selection of nozzle, with the addition of new types, is available for a variety of desoldering works.

With B tip

View the details

N61 series nozzles

T18 series tips

Soldering iron L type HAKKO FX-8805

65W

N2 Soldering iron HAKKO FX-8802



With B tip

One-hand Manual-solderfeed iron HAKKO FX-8803



SMD hot tweezer HAKKO FX-8804








High-power Desoldering gun HAKKO FR-4101

Increasing the power to 140 W from 50 W of our previous models (HAKKO 474 • 475), it can make it easy to desolder on multi-layer PWB which was never an easy job, and it can also shorten the process time.

A wide selection of nozzle, with the addition of new types, is available for a variety of desoldering works.

- Long type nozzles for narrow space
- Oval shape nozzles for flat terminals
- SS type nozzles for micro land-patterns

Click here for more information about HAKKO FR-410.




Soldering iron HAKKO FX-8801/FX-8805

Thermal conductivity has been increased by reviewing external configuration and internal structure of 900 tip series.

Now T18 and T19 tip series are selectable depend on work environment.

Click here for more information about HAKKO FX-8801/FX-8805



N2 soldering iron HAKKO FX-8802

The N2 gas runs into the nozzle assembly and covers over the soldering tip. It prevents the soldering tip and the heater from being readily oxidized and performs great role as a preheating. Two effects of N2 system, preventing oxidation or preheating effect, can improve soldering defects such as bridging, protrusion icicle, insufficient solder filling in PTH, etc.

T18 tips series are compatible with this application.

Click here for more information about HAKKO FX-8802.

N2 system required equipments



- Solder and feed with one hand
- Feed a set amount of solder with one hand
- Manual feed system is perfect for cellular manufacturing.
- Soldering work can be conducted at the pace of the operator.
- T18 tips series are compatible with this application.

Click here for more information about HAKKO FX-8803.

SMD Hot Tweezer HAKKO FX-8804

- Direct heating—less influence upon surrounding components on crowded boards.
- Easily removes SMD chips and flat packages up to 25mm.
- The collet allows easy replacement and alignment of the tips.

<u>Click here for more information about HAKKO</u> <u>FX-8804.</u>





