



Heavy Duty Adhesive

3500

Techspray offers a variety of specialty chemicals for plant maintenance. Products range from surface cleaners, equipment service chemicals, lubricants, and adhesives.



High strength, fast tacking spray adhesive

This low soak-in adhesive exhibits particular strength when bonding surfaces such as dry wall, brick and concrete block. Heavy-Duty Adhesive will also work on surfaces such as paper, plastic, foam, wood and other fabrics. Excellent for both temporary and permanent bonds.

- High strength
- Fast tacking
- Non-ozone depleting
- Water resistant
- Non-wrinkling

Product Packaging

3500-11S
Heavy Duty Adhesive
 12 oz
 12 units/case





Technical Information

Chemical & Physical Properties

Appearance	Straw-colored liquid
Flash Point	-20°C (-4°F)
Boiling Point	37.7°C (100°F)

Chemical Composition

CHEMICAL NAME	CAS #
Hexane	110-54-3
L.P.G.	68476-85-7
Acetone	67-64-1
Petroleum Distillates	64742-89-8
N-Butane	106-97-8

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
Email: tsales@techspray.com

Europe

ITW Contamination Control
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
Email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2015 Techspray, A Division of ITW



Techspray
8125 Cobb Center Drive,
Kennesaw, GA 30152
800-858-4043 • www.techspray.com